

Benefits

- Savings on your waste collection
- Tidy premises
- Space saving
- Compliance to meet your legal obligations

Features

- Top loading
- Single phase
- Compacts hazardous waste directly into drums






Orwak 5030-N HD

Technical specifications

Dimensions 5030-N HD

- A: 2165 mm B: 850 mm C: 1290 mm
- D: 2030 mm E: 1320 mm





Loading aperture

Louding upor cure	F (0
	ø560 mm
Cycle time	
,	36 secs
Press force	
Fress lorce	
	3 ton, 30 kN
Drum size	
Width:	max ø600 mm
Height:	max 1005 mm
Weight (machine))
Total:	360 kg
Noise level	
	< 70 db (A)
Protection class	

Operating power Single Phase 230 V, 50 Hz, 10 A **Paint**

IP 55

Two-part paint and powder coat with phosphatising as base

Oil volume/type

5,1 I ISO VG 32-68 SAE 10 from +5 °C and warmer

Hydraulical data

Working pressure:	110 bar
Relief pressure:	140 bar
Press force:	3 ton, 30 kN
Piston stroke:	790 mm
Press force per cm ² :	I,5 kg

An easy-to-operate top loading machine

Compacts hazardous waste, such as glass and cans/tins with paint, oil and other chemical remains directly into drums.

With Orwak 5030-N HD the handling, transportation and disposal of chemical waste becomes safe and simple.

Operator easily handles the heavy duty steel pallet with standard pallet lifter.







Standard drums can be used for storage and transport of the hazardous waste. By using several drums, sorting is possible.

Our promise to You!

- Orwak financial solutions
- · Orwak non-stop service

For further information please contact Your local Orwak dealer.

Semi-dry Waste

Tetra paks

Steel drums

Hazardous waste

Wet Juice boxes,

Special

Bagged general waste

The Orwak 5030-N HD takes care of most of your waste

Plastic foil

Shrink film

Plastic bags

Plastic containers

PET bottles Jugs/bottles

Other plastics

OK

Plastic straps

Paper Cardboard Shredded

Paper sacks Metal Cans

Aluminium cans Food cans Paint cans

Other metals Steel straps

Perfect choice

Other materials contact us

For more info. contact us or visit our website www.orwak.com We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.



AB Orwak Box 58, SE-576 22 Sävsjö, Sweden Tel: +46 382-157 00, Fax: +46 382-106 07 E-mail: info@orwak.se

